



# QUICSEAL 717

Product Name  
Lap Cement

Multi-Purpose Adhesive & Lap Cement for Felt Based Systems

## Description

QUICSEAL 717 is a cold applied felt adhesive, lap cement and gritting adhesive, for use in a multitude of applications.

## Uses

QUICSEAL 717 can be used for fixing felt to felt, concrete, metal and similar substrates. It can be used in conjunction with a multitude of waterproofing system, roofing membranes and floor slab damp proofing systems.

## Surface Preparation

Substrates to which the felt is to be adhered to should be clean and sound.

On porous substrates, apply QUICSEAL Super Penetration Primer at a rate of 0.10 litres per sqm, and allow to dry before proceeding to the next stage.

## Application

### General

Apply QUICSEAL 717 by brush or broom and after approximately 15 minutes, roll felt into position and press down firmly.

When the adhesive is nearly dry after approximately 6 hours, inspect the felt and any areas not adhering should be firmly pressed or rolled down.

### Lap Sealing

For roof applications, it is essential to seal laps to ensure they are watertight. Fix first sheet of felt to the roof parallel to the eaves.

Working up the roof, position second sheet allowing a minimum 75mm overlap on the lower sheet, fix by nailing at 600 mm centres 20 mm in from the top edge, hold back the lower edge and apply QUICSEAL 717 to the lap.

### Gritting Adhesive

QUICSEAL 717 can be used for fixing grit or chippings over asphalt or bitumen felt to provide a solar reflective coating.

Surfaces must be sound and clean and the chippings dust free.

## **Packaging**

Packing Size : 18kg/tin

## **Storage**

Do not store or use in the presence of naked flames or hot surfaces. Normal precautions against fire must be taken. The shelf life of QUICSEAL 717 is 24 months when stored unopened in a cool, dry place.

## **Health & Safety**

Remove any contamination of the skin promptly using hand cleanser, then wash with soap & water.

Treat accidental splashes in the eye by washing plenty of clean water and seek medical advice.

This product is flammable and contains hydrocarbon solvent.

## **Important Notes**

The information set forth herein is furnished free of charge in good faith and is based on technical data that QUICSEAL considers to be reliable. This information is intended for use by persons having technical skill and at their own discretion and risk. Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of QUICSEAL products as of the date of publication of this document. QUICSEAL makes no other warranties and assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, please contact QUICSEAL.

Reference No. QS717/020317

**QUICSEAL CONSTRUCTION CHEMICALS PTE LTD**

*QUICSEAL – the professional's choice of quality products and systems for building construction*